



PRODUCT INFO

LAY-IN COLORLINE NOZZLE



- Lay-in ventilation tile fitted with 360° adjustable polycarbonate ABS disks.
- Standard colour metallic silver or white. Other colours available on request.
- Nozzle disks are available in grey and white.
- Pre-painted finish.
- 600 x 600 mm.
- The tiles can easily be fitted into the Lay-in suspension structure.
- Additional, a plenum is available with a side connector of 160 or 200 mm.

ceilux lay-in	46006



LAY-IN NOZZLE R

64 diffusers

Installation height	min - max	2.2-3.3	2.7-3.4	2.8-3.4	2.9-3.5	3.0-3.6	3.1-3.7	3.2-3.9	3.4-4.0	3.4-4.1
Noise level [dB]	dB	<20	20	25	30	35	40	45	50	55
Air delivery speed	m/s	2	3	4	5	6	8	9	10	12
Pressure drop	Pa	7	13	22	32	43	70	86	103	140
Air/flow	m³/h	119	178	238	298	357	476	535	594	714
Throw	m	0.9	1.4	1.8	2.3	2.8	3.7	4.2	4.6	5.5

LAY-IN NOZZLE R10

36 diffusers

Installation height	min - max	2.2-3.3	2.7-3.4	2.8-3.4	2.9-3.5	3.0-3.6	3.1-3.7	3.2-3.9	3.4-4.0	3.4-4.1
Noise level [dB]	dB	<20	20	25	30	35	40	45	50	55
Air delivery speed	m/s	2	3	4	5	6	8	9	10	12
Pressure drop	Pa	7	13	22	32	43	70	86	103	140
Air/flow	m³/h	67	100	134	167	201	268	301	334	401
Throw	m	0.5	0.8	1.0	1.3	1.5	2.1	2.3	2.6	3.1

Fire reaction pre and postpainted tiles: A2s1d0

Release of dangerous substances: none

Flexion resistance: Classe 1

Durability galvanized tiles: B

Durability pre and post-painted tiles: C